



DMON-6S

**1 to 6 Channel Multi-Viewer
with SDI and HDMI OUTPUTS for 3G/HD/SD
and Custom Layouts**

PRODUCT FEATURES

- Low cost (3G/HD/SD)-SDI 1 to 6 Multi-Viewer or 6 to 1 input multiplexer
- Custom Layouts with various standard layouts
- Fast switching between inputs using Full-Screen scaling
- Selectable output format in both Full-Screen Multi-viewer mode
- Low latency buffering for each input allowing non-synchronous inputs
- Linked (3G/HD/SD)-SDI and HDMI outputs
- 6 x (3G/HD/SD)-SDI inputs with auto detection (26 Formats supported in total)
- 6 x (3G/HD/SD)-SDI active loop copies of each input
- Each quadrant is independent of the others, allowing any 3G/HD/SD format of any frame rate to be displayed simultaneously
- Variable aspect ratios per quadrant
- In Pass-Through mode the selected input is passed through to both the (3G/HD/SD)-SDI and HDMI outputs
- The DMON-6S is a truly portable converter, that incorporates our new easy to use LCD and button control system. This gives you easy access to most of the amazing features without using complicated LED/button control, dip switches or having to carry around a computer to change a simple setting.
- This unit also includes:
 - 32 GPI on 37-pin DSUB for Dynamic Tallies
 - RS422/485 on 37-pin DSUB for Dynamic Tallies
 - USB port for control and firmware updates
 - Robust Aluminium box
 - Metal Thread Locking DC Power Socket
 - Power Supply, HDMI Cable and USB Cable



SPECIFICATIONS

SDI INPUT & OUTPUT FORMATS	3G: SMPTE 424M@2.97 and 2.967Gb/s <ul style="list-style-type: none"> • 1080p@60/59.94/50Hz HD: SMPTE 292M/274M/296M@1.485 and 1.435Gb/s <ul style="list-style-type: none"> • 1080i@60/59.94/50Hz • 1080p/psf@30/29.97/25/24/23.98Hz • 720p@60/59.94/50/30/29.97/25/24/23.98Hz SD: SMPTE 259M@270Mb/s <ul style="list-style-type: none"> • 625i50 • 525i59.94 	LCD / BUTTON MENU OPTIONS	<ul style="list-style-type: none"> • HDMI output type • Output Select • Multi-Viewer Output Format • Multi-Viewer Number of Windows • Multi-Viewer Layout • Multi-Viewer Audio Source • Multi-Viewer Reference • Full Screen is Scaled • Input Routing • GPI mode • Setup
HDMI OUTPUT FORMATS	<ul style="list-style-type: none"> • 1080p@60/59.94/50Hz • 1080i@60/59.94/50Hz • 1080p@30/29.97/25/24/23.98Hz • 720p@60/59.94/50/30/29.97/25 • 625i50 / 525i59.94 	INPUTS	<ul style="list-style-type: none"> • 6 x (3G/HD/SD)-SDI • Input Equalization > 100M using Belden 1694A • USB for control and updates
LED STATUS	<ul style="list-style-type: none"> • Power • 6 x Signal lock and rate 	OUTPUTS	<ul style="list-style-type: none"> • 6 x SDI (3G/HD/SD)-SDI Active Loop-throughs • 2 x SDI (3G/HD/SD)-SDI • HDMI Type A
POWER	<ul style="list-style-type: none"> • +5V to +32V DC • Positive Centre Pin 	DIMENSIONS	220mm x 103.7mm x 29.5mm (8.7" x 4.1" x 1.2")

DISTRIBUTED BY:

www.decimator.com

Innovative Monitoring Solutions

Copyright © 2014 DECIMATOR DESIGN PTY LTD DMON-6S BROCHURE V1.0