


The SPACE Product Range



SPACE+

Rack Based Facility NAS

Higher capacity SPACE+ pushes SPACE to greater performance and is designed to be used directly across the network with an abundance of sustained, reliable performance and comprehensive CORE.4 workflow tools.

Ideal for Film, Post-Production and Facilities.


Technologies:

IDA² / Dynamic Bandwidth /
Analytics Centre / CloakDR /
Mosaic

Capacity: 128 - 224TB

Speed: Up to 3GB/s

Expandable: Up to 4PB





SPACE+ Tech RFI

Unit specifications

Unit dimensions: 13.2cm x 43.7cm x 64.8cm (5.1" x 17.2" x 25.5")
Unit weight: 33kg (72.7lbs)
Input range: 100 - 240 VAC, 50-60Hz
PSU safety: EMC - USA-UL listed. Canada-CUL listed, Germany-TUV certified, EN60950/IEC 60950-Compliant, CB report, CCC certification
Power supply: Dual redundant 1000W removable PSUs
Power requirements standby: 33W
Power requirements full load: 350W
Operating temperature range: 10°C - 35°C
Non-operating range: -40°C - 70°C
Operating humidity range: 8 - 90% non-condensing
Non-operating humidity range: 5 - 95% non-condensing
Unit form factor: 3U rackmount (rack mounts included)

Bootable replacement OS is provided on Rescue Capsule USB drive for fast system recovery.

Configurable capacities

SPACE+ 128TB, 160TB, 192TB and 224TB
SPACE EX 32TB, 64TB, 128TB, 160TB, 192TB and 224TB (Up to 4PB)

Connectivity

On Motherboard

4 x USB 3.0 ports	2 x 10Gb Ethernet ports (RJ45) -
1 x VGA connector	Backwards compatible with 1Gb
1 x COM port	Ethernet (RJ45)
	1 x RJ45 dedicated IPMI LAN port

Other

2 x 40/100Gb Ethernet ports
Option for additional 1Gb, 10Gb, 25Gb, 40Gb and 100Gb Ethernet ports

Key Features

CORE.4 OS	Active Directory
Dynamic Bandwidth Control	Workspace access control
HyperSpace compatible	Mosaic
RAID 6 Data Protection	File Manager
Replication	CloakDR
Snapshots	Analytics Centre
Automation	